

# Operating Instructions for **Filter Machine Pump & Return Style** (PN:700068)

## IMPORTANT!



## PLEASE READ

- Operate equipment only after you have been properly trained.
- **DO NOT** force the tip of the filter wand into the food crumbs at the bottom of the fryer.
- No boil-out water or chemical should be put into the machine. This will void the warranty.
- After oil passes through the system all fittings and plumbing will be very **HOT**. Make sure you are wearing insulated gloves.
- Clean the machine after every filtering session. Insure the bottom of the pan is debris free.
- Always use filter paper when operating the machine. If the paper gets embedded with debris and the oil flow slows, replace the paper with new paper.

## Setup



1. Remove Lid and Screen from filter machine. Always begin setup with clean pan and fresh paper.



2. Place clean expanded metal spacer in the bottom of machine. Install filter paper evenly on top of spacer. Set retainer weight on the filter paper. Make sure there are no gaps or tears in the paper.

## Filtering the Oil



3. Put on Personal Protection Equipment before operating equipment.



4. Push the rocker switch to the left to pull oil from the fryer.



5. Insert the tip of the wand just below the surface of the oil. Do not force the tip to the bottom of fryer. The oil will flow on top of the filter paper.



6. Before sending oil back to the fryer, place the rocker switch into neutral position until motor stops.



7. After cleaning the fryer, direct the tip of the wand into the fryer, then push the rocker switch to the right to return the oil to the fryer.



8. With the tip of the wand in the clean fryer refill the fryer with filtered oil.

## Disposing the Oil



If you are going to dispose of the oil place the lid on the caddy before transporting the machine to disposal location. Press the rocker switch to the right to dispose of the used oil. (Return to fryer position)

## Tips and Troubleshooting



If the motor overloads and stops running, check the reset button behind the motor cover. Press the button very hard until you hear a loud click to reset the motor.



The screen can be used if you are pouring oil directly into the Filter Machine body.



Scan for Equipment/Parts & Service  
Buscar equipos / Piezas y servicio

[www.darpro-solutions.com](http://www.darpro-solutions.com)

ADDING VALUE THROUGH **SERVICE AND INNOVATION**

**DAR PRO**  
SOLUTIONS

**DARLING**  
INGREDIENTS